
Getting the Most Out of an Asphalt Overlay

VDOT Experiences with Pavement Recycling

Brian Diefenderfer, PhD, PE

Illinois Bituminous Paving Conference

December 12, 2018

Overview

- Background
- Examples
 - I-81
 - NCAT
 - I-64
- Summary



Background

- VDOT maintains nearly all roads in the state
 - About 128,000 lane miles
 - More than 97% has an asphalt surface
- CY 2018 planned paving
 - \$515 million
 - 8500+ miles



Background

- Main causes of pavement deterioration
 - Environment and traffic loading
- Choice of pavement rehab methods
 - Costs
 - Traffic volumes
 - Allowable work hours
 - Type and causes of deterioration



Background


- Typical rehab methods = overlay or mill and overlay
 - Addresses most needs
 - Efficiently?
 - Suitable when distresses are in upper 3 to 4 inches
- Challenges
 - Increasing costs
 - Same treatments do not last as long as they used to
 - Greater reluctance to inconvenience public
 - Consumption of natural resources



More than 10 million tons of
stockpiled RAP



Could pave a 12-foot wide lane, 12 inches deep for more than 2,300 miles



Background

- Pavement recycling can address some challenges
 - Reduced costs, environmental impact, and construction time
 - Expect similar service life to non-recycling
 - Can be easier to fix deeper issues
- Cold in-place recycling
- Cold central plant recycling
- Full depth reclamation



I-81 (2011)

- 3.7 miles
- FDR+CCPR right lane
- CIR left lane



- 29,000 AADT
- 29% trucks
- 14+ million ESALs (right lane)



I-81 (2011)



- 3.7 miles
- FDR+CCPR right lane
- CIR left lane

- 29,000 AADT
- 29% trucks
- 14+ million ESALs (right lane)



I-81 (2011)

- Performance comparison
 - Reconstruction with recycling (circles) versus single course overlay (triangles)




NCAT (2012)

S12

N3

N4





NCAT (2012)

- 3 test sections
- 2 with CCPR over aggregate base
- 1 with CCPR over FDR
- 20 million ESALs to date




NCAT (2012)

- 3 test sections
- 2 with CCPR over aggregate base
- 1 with CCPR over FDR
- 20 million ESALs to date



NCAT (2012)

- 3 test sections
- 2 with CCPR over aggregate base
- 1 with CCPR over FDR
- 20 million ESALs to date



NCAT (2012)

S12



- Section S12
- 85% recycled content
- Very low strain performance
 - Perpetual?





HEAVILY
LANE
CLOSURE



I-64

- Segment 2
 - 7.1 miles (2017-2019)
- Segment 3
 - 8.3 miles (2018-2021)
- 35,500 AADT
- 9% trucks
- New lanes
 - Imported material stabilized using an FDR process
- Existing lanes
 - Existing material under old concrete reclaimed using FDR
- All lanes include CCPR






CCPR = 85% RAP, 15% #10s
100% passing 12.5mm





SN = 7.08, \$83/SY



SN = 7.06, \$40-61*/SY



I-64, Considering Segments 2 and 3

- About 154 lane miles of new pavement constructed primarily with recycled materials
 - Includes mainline and shoulders
- More than one million tons of material will be recycled
- Compared to a non-recycling design, cost savings exceed \$15 million




I-64

- Annual performance monitoring
 - Ride quality, rut depth, and cracking measurements
- Instrumented test section



- Pressure cell on top of OGDL
- Pressure cell on top of subgrade
- ≡ Horizontal asphalt strain
- Temperature probe array
- ▲ TDR moisture probe array





Summary

- Recycling can address some pavement rehab challenges and increase the life of an asphalt overlay
 - Including on high volume pavements
- Further study needed to identify:
 - Expected service life
 - Failure mechanisms
 - Practical methods of QA





We bring innovation to transportation.

Thank you!

brian.diefenderfer@vdot.virginia.gov